



FLEXYLED SHE6 PW PRO

Domus Line design

Flexible pre-wired LED modules sliding

Materials:
flexible LED strip without adhesive

Covering:
high reflectance paint

Light source:
static light LED module

Number of LEDs:
180 LED/metre



Application type:
universal

Installation:
slide inside small profiles



TECHNICAL DATA

Power	14,4W/m
Power supply	24Vdc
LEDs/metre	180
Divisibility	3,3cm (6 LED)
Cable	2000mm
Protection	IP20
Adhesive 3M®	no



FLEXYLED SHE6 PW PRO is an LED strip with **180 LED/m** on a circuit of only **6 mm wide**. Developed to be integrated **"sliding" within small profiles** (e.g. APEX), it is supplied in modules of 100 cm, 200 cm, 250 cm and 300 cm with power supply and connector (pre-wired). These modules are designed with **reinforced soldered power supply cable terminals** which ensure good solidity.



Colour appearance	natural white
Colour temperature	4200 Kelvin
Luminous efficiency	85 lm/W
CRI	Ra ≥ 80




Colour appearance	warm white
Colour temperature	3100 Kelvin
Luminous efficiency	85 lm/W
CRI	Ra ≥ 80



Colour appearance	super warm white
Colour temperature	2700 Kelvin
Luminous efficiency	85 lm/W
CRI	Ra ≥ 80

* values referring to FLEXYLED SHE6 PW PRO 1000mm

A PRODUCT AVAILABLE. VALIDATED TECHNICAL AND PHOTOMETRIC DATA.



FLEXYLED SHE6 PW PRO
modules with 180 LED/metre



Code	Length	Watt & Volt	Light colour	LED
1382601N/SHE	1000mm	14,4W @ 24Vdc	natural white	180
1382601B/SHE	1000mm	14,4W @ 24Vdc	warm white	180
1382601B1/SHE	1000mm	14,4W @ 24Vdc	super warm white	180
1382701N/SHE	2000mm	28,8W @ 24Vdc	natural white	360
1382701B/SHE	2000mm	28,8W @ 24Vdc	warm white	360
1382701B1/SHE	2000mm	28,8W @ 24Vdc	super warm white	360
1382801N/SHE	2500mm	36W @ 24Vdc	natural white	450
1382801B/SHE	2500mm	36W @ 24Vdc	warm white	450
1382801B1/SHE	2500mm	36W @ 24Vdc	super warm white	450
1382901N/SHE	3000mm	43,2W @ 24Vdc	natural white	540
1382901B/SHE	3000mm	43,2W @ 24Vdc	warm white	540
1382901B1/SHE	3000mm	43,2W @ 24Vdc	super warm white	540

CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.



This profile integrates a stripled with OSRAM Opto Semiconductors diodes.



For LED converters and accessories consult the **Domus Extra catalogue** also available on www.domusline.com.



¹ For UL-certified model codes, see the **American standard LED collection catalogue**, also available at www.domusline.com.



Compatible with:

- APEX
- APEX H7
- MISS*
- LAB*

* can integrate APEX profile

For details see the **Flexyled collection catalogue** also available on www.domusline.com

