



FLEXYLED UHE6 PW

Domus Line design

Flexible pre-wired sliding LED modules

Materials:

flexible LED strip without adhesive

Covering:

high reflectance paint

Light source:

static light LED module

Number of LEDs:

280 LED/metre



Application type:

universal



Installation:

slide inside small profiles

FLEXYLED UHE6 PW is an LED strip with **280 LED/m** on a circuit of only **6 mm wide**. Developed to be integrated **“sliding” within small profiles** (e.g. APEX), it is supplied in modules of 100 cm, 200 cm, 250 cm and 300 cm with power supply and connector (pre-wired). These modules are designed with **reinforced soldered power supply cable terminals** which ensure good solidity.



Colour appearance natural white
Colour temperature 4000 Kelvin
Luminous efficiency 82 lm/W
CRI Ra ≥ 80



Colour appearance warm white
Colour temperature 3000 Kelvin
Luminous efficiency 82 lm/W
CRI Ra ≥ 80

* values refer to FLEXYLED UHE6 PW 1000 mm

TECHNICAL DATA

Power	10W/m
Power supply	24Vdc
LEDs/metre	280
Divisibility	2.5 cm (7 LED)
Cable	2000 mm
Protection	IP20
Adhesive 3M®	no



* can integrate APEX profile




FLEXYLED UHE6 PW
modules with 280 LED/metre



Code	Length	Watt & Volt	Light colour	LED
1349301N/UHE	1000mm	10W @ 24Vdc	natural white	280
1349301B/UHE	1000mm	10W @ 24Vdc	warm white	280
1349401N/UHE	2000mm	20W @ 24Vdc	natural white	560
1349401B/UHE	2000mm	20W @ 24Vdc	warm white	560
1349501N/UHE	2500mm	25W @ 24Vdc	natural white	700
1349501B/UHE	2500mm	25W @ 24Vdc	warm white	700
1349601N/UHE	3000mm	30W @ 24Vdc	natural white	840
1349601B/UHE	3000mm	30W @ 24Vdc	warm white	840

LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.



¹ For codes for UL-certified models, consult the catalogue for the **American standard LED collection** also available at www.domusline.com.



FOR LED
CONVERTERS
AND ACCESSORIES
SEE PAGE 68.