



FLEXYLED UHE6B PW

Domus Line design

Flexible pre-wired LED modules to be integrated

Materials:
flexible LED strip with adhesive

Covering:
high reflectance paint



Light source:
static light LED module

Number of LEDs:
280 LED/metre



Application type:
universal

Installation:
surface or integrated into the profiles

FLEXYLED UHE6B PW is an LED strip with **280 LED/m** on a circuit of only **6 mm wide**. It is supplied with a **high adherence 3M® adhesive** base so it can be installed into profiles with a removable diffuser. These modules are designed with **reinforced soldered power supply cable terminals** which ensure good solidity.



Colour appearance natural white
Colour temperature 4000 Kelvin
Luminous efficiency 82 lm/W
CRI Ra ≥ 80



Colour appearance warm white
Colour temperature 3000 Kelvin
Luminous efficiency 82 lm/W
CRI Ra ≥ 80

* values refer to FLEXYLED UHE6B PW 1000 mm

TECHNICAL DATA

Power	10W/m
Power supply	24Vdc
LEDs/metre	280
Divisibility	2.5 cm (7 LED)
Cable	2000 mm
Protection	IP20
Adhesive 3M®	yes


Compatible with:	
DIVA	60
GOCCIA	65
ICY	61
KOBI	67
LEDYE	61
MICY	62
SKYLINE	66
SPLITTY	60
THEA	63
TWIG	64
TWIG XO	64
TWIG XA	63



FLEXYLED UHE6B PW
modules with 280 LED/metre



Code	Length	Watt & Volt	Light colour	LED
1349701N/UHE	1000mm	10W @ 24Vdc	natural white	280
1349701B/UHE	1000mm	10W @ 24Vdc	warm white	280
1349801N/UHE	2000mm	20W @ 24Vdc	natural white	560
1349801B/UHE	2000mm	20W @ 24Vdc	warm white	560
1349901N/UHE	2500mm	25W @ 24Vdc	natural white	700
1349901B/UHE	2500mm	25W @ 24Vdc	warm white	700
1350001N/UHE	3000mm	30W @ 24Vdc	natural white	840
1350001B/UHE	3000mm	30W @ 24Vdc	warm white	840



LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.



¹ For codes for UL-certified models, consult the catalogue for the **American standard LED collection** also available at www.domusline.com.



FOR LED CONVERTERS AND ACCESSORIES SEE PAGE 68.