



ACANTHUS 2.0

Domus Line design

Recessed LED spotlight

Materials:

metal alloy, thermoplastic polymers

Finishes:

gold plated, chrome plated antique bronze, antique gold, antique silver, oriental silver

Light source:

SMD LED module

Wiring:

79" (2000mm)







Installation:

recessed

Application type:

inside cabinet, under cabiner, under shelf

Patented



Colour appearance natural white

Colour temperature 4300 K

Luminous flux 390 lm

Luminous efficiency 130 lm/W

CRI Ra ≥ 80

Colour appearance warm white

Colour temperature 3000 K

Luminous flux 360 lm

Luminous efficiency 120 lm/W

CRI Ra ≥ 80

Colour appearance super warm white

Colour temperature 2700 K

Luminous flux 360 lm

Luminous efficiency 120 lm/W

CRI Ra ≥ 80



ACANTHUS 2.0


installation on wood panels



Code	Watt & Volt	Light colour
13481__N	3W @ 12Vdc	natural white
13481__B	3W @ 12Vdc	warm white
13481__B1	3W @ 12Vdc	super warm white

LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.

Code	Finish
08	gold plated
09	chrome plated
18	antique bronze
38	antique gold
37	antique silver
40	oriental silver



FOR LED CONVERTERS AND ACCESSORIES SEE PAGE 200.

INSTALLATION

The devices are designed for flush mounting with a Ø 2-11/16" (68mm) hole. The fixing system, with two lateral steel springs, is quick and does not require any tools.



FINISHES



GOLD PLATED (code 08)



CHROME PLATED (code 09)



ANTIQUE BRONZE (code 18)



ANTIQUE GOLD (code 38)



ANTIQUE SILVER (code 37)



ORIENTAL SILVER (code 40)