



APEX 86 SP

Domus Line
design

Surface aluminium LED profile

Materials:

aluminium, polycarbonate,
thermoplastic polymers

Finishes:

aluminium, black matt

Light source:

SHE LED module (168 LED/m)

Wiring:

2000mm



Application type:

under shelf



Installation:

surface

APEX 86 SP is designed for under shelf surface application and the profile design guarantees a 180° light projection. Its length can be adapted to your needs, with a minimum of 300 mm and a maximum of 3000 mm. Installation is quick and easy using the screws supplied.



Colour appearance natural white
Colour temperature 3900 K
Luminous efficiency 60 lm/W
CRI Ra ≥ 80



Colour appearance super warm white
Colour temperature 2700 K
Luminous efficiency 60 lm/W
CRI Ra ≥ 80

* values referring to APEX 86 SP 1000mm

A PRODUCT AVAILABLE. VALIDATED TECHNICAL AND PHOTOMETRIC DATA.



APEX 86 SP


without switch




Code	Model	Watt & Volt
on request*	SHE (168 LED/m)	10W @ 24Vdc

CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.

* Codes will be provided according to the length requested.



FINISHES



ALUMINIUM (code 05)



BLACK MATT (code 32)

For LED converters and accessories consult the **Domus Extra catalogue** also available on www.domusline.com.

