



FLEXYLED SE H4-24 D-M

flexible linear LED profile with double power cable



Code	Length	Watt	Volt	CCT
1504701/TWA/200	2000mm	19,2 W/m	24 VDC	2700 - 4000 K
1504701/TWA/300	3000mm	28,8 W/m	24 VDC	2700 - 4000 K



CLIPS

Stainless steel clips for supports with minimum 13 mm - maximum 22 m thickness, sold separately.

code: 4012600



values referring to FLEXYLED SE H4-24 D-M 1000mm

Colour appearance	D-Motion white
Colour temperature	2700 - 4000 K
Luminous flux	770 lm/m
Luminous efficiency	80 lm/W
CRI	Ra 90

FLEXYLED SE H4-24 D-M

flexible LED profile with double power cable

FLEXYLED SE H4-24 D-M is a dual-colour D-Motion flexible linear LED profile made of co-extruded reflective and diffusing silicone materials, with 144 +144 LEDs/m, designed to be recessed in a milled groove flush with the panel, or integrated in aluminium profiles. Thanks to its flexibility, FLEXYLED SE H4-24 DM can also be installed on curved milled groove, ring or any other configuration, press-fitted without glue or adhesives. Stainless steel clips for installation on 13-22 thick panels are also available. The LED profile can be divided at 41.67 mm (6+6 LED) intervals. FLEXYLED SE H4-24 D-M is available in 2000mm and 3000mm long rolls with 2000 mm long double power cable featuring Micro24 connectors. Power supply not included. To be ordered separately.



This product contains a light source of energy efficiency class **G**.