



HAMPTON 2.0

Domus Line design

Recessed LED spotlight

Materials:

metal alloy, thermoplastic polymers

Finishes:

antique gold, antique pewter, brown, antique copper

Light source:

SMD LED module

Wiring:

79" (2000mm)



Installation:

recessed



Application type:

inside cabinet, under cabiner, under shelf



Patented




Colour appearance natural white
Colour temperature 4300 K
Luminous flux 390 lm
Luminous efficiency 130 lm/W
CRI Ra ≥ 80



Colour appearance warm white
Colour temperature 3000 K
Luminous flux 360 lm
Luminous efficiency 120 lm/W
CRI Ra ≥ 80



Colour appearance super warm white
Colour temperature 2700 K
Luminous flux 360 lm
Luminous efficiency 120 lm/W
CRI Ra ≥ 80



HAMPTON 2.0

installation on wood panels



Code	Watt & Volt	Light colour
13654__N	3W @ 12Vdc	natural white
13654__B	3W @ 12Vdc	warm white
13654__B1	3W @ 12Vdc	super warm white

Code	Finish
29	antique pewter
38	antique gold
39	brown
43	antique copper

LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.



FOR LED CONVERTERS AND ACCESSORIES SEE PAGE 200.

INSTALLATION

The devices are designed for flush mounting with a Ø 2-11/16" (68mm) hole. The fixing system, with two lateral steel springs, is quick and does not require any tools.



FINISHES



ANTIQUPEWTER (code 29)



ANTIQUPEWTER (code 38)



BROWN (code 39)



ANTIQUPEWTER (code 43)