



## FLEXYLED HE PW

Domus Line design

**Flexible pre-wired LED modules to be integrated**

**Materials:**  
flexible LED strip with adhesive



**Covering:**  
high reflectance paint

**Light source:**  
static light LED module



**Application type:**  
universal

**Installation:**  
surface or integrated in the profiles

**FLEXYLED HE PW** is an LED strip with **37 LED/ft (120 LED/m)** on a circuit of only **5/16" (8 mm)** wide with adhesive base. Developed to be installed inside profiles with a removable diffuser, these are supplied in modules of **3.3 ft (1m)**, **6.6 ft (2m)**, **8.2 ft (2.5m)** and **9.8 ft (3m)** with power supply and connector (pre-wired).



**Colour appearance** natural white  
**Colour temperature** 4300 Kelvin  
**Luminous efficiency** 85 lm/W  
**CRI** Ra ≥ 80




**Colour appearance** warm white  
**Colour temperature** 3100 Kelvin  
**Luminous efficiency** 85 lm/W  
**CRI** Ra ≥ 80

\* values refer to FLEXYLED HE PW 39-3/8" (1000mm)

### TECHNICAL DATA

<b>Power</b>	2.9 W/ft (9.6W/m)
<b>Power supply</b>	24Vdc
<b>LEDs/ft (LEDs/metre)</b>	37 (120)
<b>Divisibility</b>	1-31/32" (5cm) - 6 LED
<b>Cable</b>	79" (2000mm)
<b>Protection</b>	IP20
<b>Adhesive 3M®</b>	yes

Compatible with:	
DIVA	134
GOCCIA	138
ICY	134
KOBI	138
LEDYE	135
MICY	135
THEA	136
TWIG	137
TWIG XO	137
TWIG XA	136



**FLEXYLED HE PW**

modules with 37 LED/ft (120 LED/metre)



Code	Length	Watt & Volt	Light colour	LED
1289801NC/HE	3.3 ft (1000mm)	9.6W @ 24Vdc	natural white	120
1289801BC/HE	3.3 ft (1000mm)	9.6W @ 24Vdc	warm white	120
1289901NC/HE	6.6 ft (2000mm)	19.2W @ 24Vdc	natural white	240
1289901BC/HE	6.6 ft (2000mm)	19.2W @ 24Vdc	warm white	240
1290001NC/HE	8.2 ft (2500mm)	24W @ 24Vdc	natural white	300
1290001BC/HE	8.2 ft (2500mm)	24W @ 24Vdc	warm white	300
1290101NC/HE	9.8 ft (3000mm)	28.8W @ 24Vdc	natural white	360
1290101BC/HE	9.8 ft (3000mm)	28.8W @ 24Vdc	warm white	360

**LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.**



FLEXYLED HE PW (12Vdc) with modules divisible every 63/64" (2.5 cm) - 3 LED pre-wired and Micro12 connector is available upon request.



FOR POWER SUPPLIES AND ACCESSORIES SEE PAGE 200.