



## FLEXILED HE6 PW PRO

Domus Line design

**Flexible pre-wired LED modules sliding**

**Materials:**  
flexible LED strip without adhesive

**Covering:**  
high reflectance paint

**Light source:**  
static light LED module

**Number of LEDs:**  
120 LED/metre



**Application type:**  
universal

**Installation:**  
slide inside small profiles



### TECHNICAL DATA

<b>Power</b>	9.6W/m
<b>Power supply</b>	24Vdc
<b>LEDs/metre</b>	120
<b>Divisibility</b>	5 cm (6 LED)
<b>Cable</b>	2000 mm
<b>Protection</b>	IP20
<b>Adhesive 3M®</b>	no



**FLEXILED HE6 PW PRO** is an LED strip with **120 LED/m on a circuit of only 6 mm wide**. Developed to be integrated **"sliding" within small profiles** (e.g. APEX), it is supplied in modules of 100 cm, 200 cm, 250 cm and 300 cm with power supply and connector (pre-wired). These modules are designed with **reinforced soldered power supply cable terminals** which ensure good solidity.



**Colour appearance** natural white  
**Colour temperature** 4200 Kelvin  
**Luminous efficiency** 85 lm/W  
**CRI** Ra ≥ 80




**Colour appearance** warm white  
**Colour temperature** 3100 Kelvin  
**Luminous efficiency** 85 lm/W  
**CRI** Ra ≥ 80



**Colour appearance** super warm white  
**Colour temperature** 2700 Kelvin  
**Luminous efficiency** 85 lm/W  
**CRI** Ra ≥ 80

\* values referring to FLEXILED HE6 PW PRO 1000mm

**A** PRODUCT AVAILABLE. VALIDATED TECHNICAL AND PHOTOMETRIC DATA.



**FLEXYLED HE6 PW PRO**  
modules with 120 LED/metre



Code	Length	Watt & Volt	Light colour	LED
1381801N/HE	1000mm	9,6W @ 24Vdc	natural white	120
1381801B/HE	1000mm	9,6W @ 24Vdc	warm white	120
1381801B1/HE	1000mm	9,6W @ 24Vdc	super warm white	120
1381901N/HE	2000mm	19,2W @ 24Vdc	natural white	240
1381901B/HE	2000mm	19,2W @ 24Vdc	warm white	240
1381901B1/HE	2000mm	19,2W @ 24Vdc	super warm white	240
1382001N/HE	2500mm	24W @ 24Vdc	natural white	300
1382001B/HE	2500mm	24W @ 24Vdc	warm white	300
1382001B1/HE	2500mm	24W @ 24Vdc	super warm white	300
1382101N/HE	3000mm	28,8W @ 24Vdc	natural white	360
1382101B/HE	3000mm	28,8W @ 24Vdc	warm white	360
1382101B1/HE	3000mm	28,8W @ 24Vdc	super warm white	360

**CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.**

24Vdc



This profile integrates a stripled with OSRAM Opto Semiconductors diodes.



For LED converters and accessories consult the **Domus Extra catalogue** also available on [www.domusline.com](http://www.domusline.com).



<sup>1</sup> For UL-certified model codes, see the **American standard LED collection catalogue**, also available at [www.domusline.com](http://www.domusline.com).



Compatible with the profiles:

- APEX
- APEX H7
- MISS\*
- LAB\*

\* can integrate APEX profile

For details see the **Flexyled collection catalogue** also available on [www.domusline.com](http://www.domusline.com)

