

## FLEXYLED UHE10 PW

Domus Line design

**Flexible pre-wired LED modules to be integrated**

**Materials:**  
flexible LED strip with adhesive



**Covering:**  
high reflectance paint

**Light source:**  
static light LED module



**Application type:**  
universal

**Installation:**  
surface or integrated into the profiles

**FLEXYLED UHE10 PW** is an LED strip with **73 LED/ft (240 LED/m)** on a circuit of **13/32" (10 mm)** wide with adhesive base. Developed to be installed inside profiles with a removable diffuser, these are supplied **in modules of 3.3 ft (1m), 6.6 ft (2m), 8.2 ft (2.5m) and 9.8 ft (3m)** with power supply and connector (pre-wired). Modules with custom lengths are available upon request.



**Colour appearance** natural white  
**Colour temperature** 4000 Kelvin  
**Luminous efficiency** 70 lm/W  
**CRI** Ra ≥ 80



**Colour appearance** warm white  
**Colour temperature** 3100 Kelvin  
**Luminous efficiency** 70 lm/W  
**CRI** Ra ≥ 80

\* values refer to FLEXYLED UHE10 PW 39-3/8" (1000mm)

### TECHNICAL DATA

<b>Power</b>	5.9W/ft (19,2W/m)
<b>Power supply</b>	24Vdc
<b>LEDs/ft (LEDs/metre)</b>	73 (240)
<b>Divisibility</b>	1-31/32" (5cm) - 6 LED
<b>Cable</b>	79" (2000mm)
<b>Protection</b>	IP20
<b>Adhesive 3M®</b>	yes





**FLEXYLED UHE10B PW**

modules with 73 LED/ft (240 LED/metre)



Code	Length	Watt & Volt	Light colour	LED
1350101N/UHE	3.3 ft (1m)	19.2W @ 24Vdc	natural white	240
1350101B/UHE	3.3 ft (1m)	19.2W @ 24Vdc	warm white	240
1350201N/UHE	6.6 ft (2m)	38.4W @ 24Vdc	natural white	480
1350201B/UHE	6.6 ft (2m)	38.4W @ 24Vdc	warm white	480
1350301N/UHE	8.2 ft (2.5m)	48W @ 24Vdc	natural white	600
1350301B/UHE	8.2 ft (2.5m)	48W @ 24Vdc	warm white	600
1350401N/UHE	9.8 ft (3m)	57.6W @ 24Vdc	natural white	720
1350401B/UHE	9.8 ft (3m)	57.6W @ 24Vdc	warm white	720

**LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.**



FOR POWER SUPPLIES AND ACCESSORIES SEE PAGE 200.