



X-SIGN 4F

Domus Line
design

LED luminaire for wall-mounting

Materials:

PMMA, thermoplastic polymers,

Finishes:

white, steel

Light source:

LGP LED module

Wiring:

79" (2000mm)

Application type:



universal

Installation:



on the wall

Patented

X-SIGN 4F, thanks to its distinctive and functional design, is a product suitable for wall applications. The diffuser guarantees perfect opalescence and the thin luminaire support, designed to enhance it, is available in white and steel finishes. **X-SIGN 4F** integrates a special LGP cluster, which ensures high performance and a wide projection beam.



Colour appearance	natural white
Colour temperature	3900 K
Luminous flux	480 lm
Luminous efficiency	48 lm/W
CRI	Ra ≥ 80



Colour appearance	warm white
Colour temperature	2800 K
Luminous flux	400 lm
Luminous efficiency	40 lm/W
CRI	Ra ≥ 80




X-SIGN 4F
without switch



Code	Watt & Volt	Light colour
13283__N/1	10W @ 24Vdc	natural white
13283__B/1	10W @ 24Vdc	warm white

Code	Finish
01	white
19	steel

ALIMENTATORE NON INCLUSO. DA ORDINARE SEPARATAMENTE.



FOR POWER SUPPLIES AND ACCESSORIES SEE PAGE 200.




X-SIGN 4F TDM
with master touch dimmable switch



Code	Watt & Volt	Light colour
13283__N/2	10W @ 24Vdc	natural white
13283__B/2	10W @ 24Vdc	warm white

Code	Finish
01	white
19	steel

LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.



X-SIGN 4F TDM integrates a master dimmable touch electronic switch that allows switching on, switching off and adjusting the light intensity of the individual luminaire and all the luminaires connected to it.



SETS OF 2, 3, 4, 5 **X-SIGN 4F** AND POWER SUPPLY ARE AVAILABLE ON REQUEST.

FINISHES



WHITE (code 01)



STEEL (code 19)