



FLEXYLED HE FS

Domus Line
design

Flexible pre-wired full spectrum LED modules to be integrated

Materials:

flexible LED strip with adhesive

Covering:

high reflectance paint

Light source:

full spectrum LED module

Number of LEDs:



120 LED/m

Application type:

universal

Installation:

surface or integrated in the profiles



* values referring to FLEXYLED HE FS 1000mm

Colour appearance natural white
Colour temperature 4000 K
Luminous efficiency 95 lm/W
CRI Ra ≥ 98




FLEXYLED HE FS PW

120 LED/m module



| Code | Length | Watt & Volt |
|------|--------|-------------|
| | 1000mm | 18W @ 24Vdc |
| | 2000mm | 36W @ 24Vdc |
| | 3000mm | 54W @ 24Vdc |

LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.



TECHNICAL DATA

- Power** 18 W/m
- Power supply** 24Vdc
- LEDs/metre** 120
- Divisibility** 5cm (6 LED)
- Power cable** 2000mm
- Protection** IP20
- Adhesive 3M®** yes

Compatible with*:

- DIVA
- ICY
- LEDYE
- MICY
- TWIG
- TWIG XO
- TWIG XA



It's recommended installing FLEXYLED HE FS on surfaces suitable for heat dissipation (e.g. aluminium profiles).

* For profiles and accessories browse the **Flexyled collection catalogue**.



For power supplies and accessories browse the **Domus Extra catalogue**.

