



QUADRUN 24

Domus Line
design

LED spotlight with diffuse light projection

Materials:

thermoplastic polymers, PMMA

Finishes:

aluminium, steel, black touch,
dark stainless, white matt

Light source:

SMD LED module

Connector:

Micro24

Wiring:

2000mm





Application type:

universal

Installation:

recessed

Patented



QUADRUN PLUS 24 is a spotlight designed for **recessed installation in a hole Ø57mm and just 12mm deep**. It is installed on wood panels with both through and blind holes. The fixing system, with two steel clamping springs, is easy to install without the use of tools.

QUADRUN PLUS 24 incorporates a high-performance SMD LED module with no-dot effect technology, ensuring a uniform projection beam without the dot effect.

Colour appearance	natural white
Colour temperature	4300 K
Luminous flux	390 lm
Luminous efficiency	130 lm/W
CRI	Ra ≥ 80

Colour appearance	super warm white
Colour temperature	2700 K
Luminous flux	360 lm
Luminous efficiency	120 lm/W
CRI	Ra ≥ 80



QUADRUN PLUS 24




Code	Watt & Volt	Light colour
	3W @ 24Vdc	natural white
	3W @ 24Vdc	super warm white

LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.



Code	Finish
10	aluminium
19	steel
46	black touch
50	dark stainless
54	white matt



(N) This drawing shows the spotlight's overall dimensions. See installation manual for more details.



QUADRUN PLUS 24 features the innovative **Plug&Play system (patented)**, for easy disconnection of the power cord from the spotlight.

FINISHES



ALUMINIUM (code 10)



STEEL (code 19)



BLACK TOUCH (code 46)



DARK STAINLESS (code 50)



WHITE MATT (code 54)

For LED converters and accessories consult the **Domus Extra catalogue** also available on www.domusline.com.

