



### FLEXYLED SHEP6B D-M

flexible linear LED roll without cable



Code	Length	Watt	Volt	CCT
F0206000001	20m	10 W/m	24 VDC	3000 - 4000 K



### FLEXYLED SHEP6B D-M PW

flexible linear LED module with cable

Code	Length	Watt	Volt	CCT
on request	on request	10 W/m	24 VDC	3000 - 4000 K



\* values referring to FLEXYLED SHEP6B D-M 500mm

<b>Colour appearance</b>	D-Motion white
<b>Colour temperature</b>	3000 - 4000 K
<b>Luminous flux</b>	840 lm/m
<b>Luminous efficiency</b>	84 lm/W
<b>CRI</b>	Ra 95

## FLEXYLED SHEP6B D-M

### Flexible linear LED module

FLEXYLED SHEP6B D-M is a dimmable dual-colour D-Motion light source developed on a 6mm-wide linear flexible module with 204+204 LED/m, designed for installation in profiles with a removable diffuser. The module, which can be divided at 29.4mm (6+6 LED) intervals, is supplied with an adhesive base. FLEXYLED SHEP6B D-M is available in 20 m long rolls without a power cable, compatible with the CH6 connection system. Modules with customised length, 2000 mm power cable and Micro24 male connector (pre-wired PW version) are available on request. Power supply not included. To be ordered separately.

