



TENDY DIY PROFILE

extruded aluminium

Code	Lenght	Finish
F0006000285	2000mm	alluminium
F0006000286	3000mm	alluminium
F0006000287	2000mm	black matt
F0006000288	3000mm	black matt



TENDY DIY DIFFUSER

extruded polycarbonate

Code	Lenght	Finish
3054801B/200	2000mm	white
3054801B/300	3000mm	white



TENDY DIY ENDS AND BRACKETS


Code	QTY	Finish
F0007000075	DX SX	alluminium
F0007000076	DX SX	black



CABLE DUCT

9x5 wireway

Code	Lenght	Finish
3071401/2000	2000mm	white
3071403/2000	2000mm	black



TENDY DIY

LED profile for kitchen units

TENDY DIY is a profile with asymmetric light projection toward the front side, designed for installation on the sides of kitchen base cabinets and recommended for use inside pull-out drawers. The mounting system allows TENDY to be installed using brackets and screws (included in the package). The fixture integrates LED modules with a 6mm wide adhesive base.

TENDY DIY

compatibility with light sources

FLEXYLED

single colour



Code	Model	Length	LED/m	Divisibility	W/m @V	Temperature	CCT	lm/m	lm/W	CRI	EEC
1590701B1/SHE	SHE6B PRO	10m	180 LED/m	33,3mm (6 LED)	14,4W/m @24VDC	super warm white	2700 K	1420	99	Ra 80	F
1590701B1/SHE	SHE6B PRO	10m	180 LED/m	33,3mm (6 LED)	14,4W/m @24VDC	warm white	3000 K	1420	99	Ra 80	F
1590701B1/SHE	SHE6B PRO	10m	180 LED/m	33,3mm (6 LED)	14,4W/m @24VDC	natural white	4000 K	1420	99	Ra 80	F
F0298000001	SHEP6B EVO	10m	216 LED/m	41,7mm (9 LED)	5,6W/m @24VDC	super warm white	2700 K	1040	186	Ra 85	C
F0298000002	SHEP6B EVO	10m	216 LED/m	41,7mm (9 LED)	5,6W/m @24VDC	warm white	3000 K	1040	186	Ra 85	C
F0298000003	SHEP6B EVO	10m	216 LED/m	41,7mm (9 LED)	5,6W/m @24VDC	natural white	4000 K	1100	196	Ra 85	B
1394101B1/UHE/2000	UHE6B	20m	280 LED/m	25mm (7 LED)	10W/m @24VDC	super warm white	2700 K	910	91	Ra 90	G
1394101B/UHE/2000	UHE6B	20m	280 LED/m	25mm (7 LED)	10W/m @24VDC	warm white	3100 K	940	94	Ra 90	F
1394101N/UHE/2000	UHE6B	20m	280 LED/m	25mm (7 LED)	10W/m @24VDC	natural white	4200 K	980	98	Ra 90	F
2508101B/2000	UHE6B CSP ULTRA	20m	280 LED/m	7,1 mm (2 LED)	10W/m @24VDC	warm white	3000 K	1120	112	Ra 94	F
2508101N/2000	UHE6B CSP ULTRA	20m	280 LED/m	7,1 mm (2 LED)	10W/m @24VDC	natural white	4000 K	1320	132	Ra 91	E

FLEXYLED D-M

dual colour



Code	Model	Length	LED/m	Divisibility	W/m @V	Temperature	CCT	lm/m	lm/W	CRI	EEC
1552701/2000	SHE6B D-M	20m	168+168 LED/m	41,7mm (7+7 LED)	10W/m @24VDC	white D-Motion	2700-4000 K	780	78	Ra 90	G
F0206000001	SHEP6B D-M	20m	204+204 LED/m	25mm (7 LED)	10W/m @24VDC	white D-Motion	3000-4000 K	780	78	Ra 90	G
F0218000007	UHE6B CSP D-M	20m	304+304 LED/m	26,3mm (8+8 LED)	10W/m @24VDC	white D-Motion	2700-4000 K	968	97	Ra 92	F
2508101/2000	UHE6B CSP ULTRA D-M	20m	240+240 LED/m	17mm (8 LED)	10W/m @24VDC	white D-Motion	2700-4000K	1120	112	Ra 91	E
2508301/2000	UHE6B CSP ULTRA D-M	20m	240+240 LED/m	17mm (8 LED)	10W/m @24VDC	white D-Motion	3000-4000K	1120	112	Ra 91	E



<https://www.domusline.com/warning-dyi-profiles/>