DOMUS LINE

FLEXYLED UHE6 CSP ULTRA

flexible linear LED reel without cable

Code	Length	Watt	Volt	CCT
2508001B/2000	20m	10W/m	24VDC	3000K
2508001N/2000	20m	10W/m	24VDC	4000K

FLEXYLED UHE6 CSP ULTRA PW

flexible linear LED reel with double power cable

Code	Length	Watt	Volt	CCT
2514801B/600	6m	10W/m	24VDC	3000K
2514801N/600	6m	10W/m	24VDC	4000K

FREE-CUT

FLEXYLED UHE6 CSP ULTRA is a FREE-CUT light source that can be cut to the desired length at any point along the reel.

FLEXYLED UHE6 CSP ULTRA, supplied without adhesive backing, is designed for slide-in installation inside micro profiles. The PW (pre-wired) version is supplied as standard in 6000 mm reels with a double power cable, allowing the strip to be cut to the required length before assembly. Reels in different lengths and versions with a single power cable are available on request.





values referred to
UHE6 CSP ULTRA 4000K 1000mm

	warm white	natural white
Colour appearance		
Colour temperature	3000 K	4000 K
Luminous flux	1120 lm/m	1320 lm/m
Luminous efficiency	112 lm/W	132 lm/W
CRI	Ra 94	Ra 91

FLEXYLED UHE6 CSP ULTRA

free-cut LED light source

FLEXYLED UHE6 CSP ULTRA is a dimmable single-colour Chip Scale Packaged light source, developed on a 6 mm-wide flexible linear module with 280 LEDs/m and designed for slide-in installation inside micro profiles. The FREE-CUT light source can be cut to the required length at any point (module approx. 7.1 mm). It is supplied without adhesive backing, either in 20 m reels without a power cable, or in the 6 m PW (pre-wired) version with two 2000 mm power cables and Micro24 connectors. Reels in different lengths and versions with a single power cable are available on request. Power supply not included; to be ordered separately.

A G E — energy efficiency class referring to CCT 4000 K

A G F — energy efficiency class referring to CCT 3000 K